www.globalminingproducts.com





Accuracy +/- 5%, Repeatability +/- 2%

Every RAD® air torque wrench is individually calibrated and traceable to NIST standards to help ensure joint integrity. RAD® tools are many times more accurate than impact wrenches and in many cases can be more precise than click type manual torque wrenches, which are often over pulled by operators.

88 times less vibration than Impact wrenches.... Operates at only 85 db

RAD® torque guns are one of the safest power tools on the market today. The exclusive low profile reaction arm takes virtually all the operational load off the operator, reducing injuries and greatly reducing operating costs. Don't wait for a time loss injury or legislation to force change in your environ-ment, RAD® guns set the standard in bolting safety.



- Smooth continuous flow of controlled torque eliminating destructive hammering and ratcheting.
- The ultimate in power-to-weight ratio! Only 3.9kgs!
- Lightweight ergonomic pistol grip design reducing operator strain and injury; resulting in increased productivity
- Versatile torque range: 400-2000 Nm.
- Controlled torque–accuracy of +/-5%, repeatability of +/-2%

RAD 20DX GenX Series Torque Tool

Part No.	Drive Size	Torque (Low- High)	RPM	Weight (kgs)	Noise Level
RAD-19135	1.0"	400 - 2000 Nm	10	3.9	80 db

All RAD 20DX Torque Tools come fully calibrated complete with:


- RAD 20DX Torque Tool
- 12" Hose & Fittings
- Reaction Arm and Retention Ring
- Ergonomic Regulator Cage and Tool Holder

To ensure the highest quality of measurement and accuracy, each RAD® pneumatic tool comes individually calibrated traceable to NIST standards.

Please contact us today

to arrange for a demonstration!

Toll Free 877-576-2855



CA	OK	ROP.			
Standard	Deep	Double	Blank	Double	Retaining
	Socket	Ended		Ended Blank	Clip
RAD-17375	RAD-18480	RAD-19094	RAD-17888	RAD-19093	RPT-17367



ALSO AVAILABLE FROM GLOBAL MINING PRODUCTS



Quick adjust torque settings Fast and accurate "dial a torque" for maximum versatility and efficiency.

Soft-start vary speed trigger Allows operator to safely and quickly set reaction arm before full torque is applied.

Equal power in forward and reverse Convenience and cost effective use of same tool for break away and final torque.

Advanced ultra-durable electric motor design

Extreme duty designed to reduce maintenance cost and increase reliability.



- ✓ Ideal for applications where compressed air or electricity is not readily available.
- ✓ DIGITAL display with colour screen
- ✓ Single Increment digital torque settings
- ✓ Fully programmable preset torque settings
- ✓ Advanced durable electric motor design



- ✓ DIGITAL and PROGRAMMABLE Pistol Grip Torque Wrenches.
- ✓ Ideal for applications where compressed air or electricity is not readily available.
- ✓ Unmatched power, VERSATILITY, and reliability in a lightweight portable tool.
- \checkmark Stall type tool capable of accuracy of +/-5%, and repeatability of +/-2%.
- Single speed and high speed models available



- ✓ Unmatched power, VERSATILITY, and reliability in a lightweight portable tool.
- ✓ Ideal for applications where compressed air or electricity is not readily available.
- Offered in both single speed and high speed models.
- \checkmark Stall type tool capable of accuracy of +/-10%, and repeatability of +/-2%.
- ✓ Quick Grip adjustable torque settings on all torque wrenches.
- ✔ Precision adjustable posi-clutch for accurate torque output.



ELECTRONIC SERIES

Torque Range 135 - 8100 Nm

- ✓ Push-button select torque Fast and convenient error-free digital single increment torque setting
- ✓ Lightweight and ergonomic pistol grip design Advance low-profile handle to reduce operator fatigue and increase productivity
- Extremely low noise level only 75db
 World's quietest extreme torque gun, ideal for sensitive environments and standards
- ✓ Data colection capability All E Series tools come with data collection software allowing traceability of each torque sequence performed
- ✓ LED Green (Pass) or Red (Fail) indicator lights Unmistakable visual signal indicates status of torque procedure for maximum accuracy and speed